



**From Concept to Reality ...  
Driving Global CO<sub>2</sub> Solutions**

**Dry Ice Pelletizers Extruders**

Standard, Economic & High Capacity

## Dry Ice Pelletizers Extruders

TOMCO<sub>2</sub> Systems' dry ice pelletizers allow you to manufacture dry ice pellets in your own facility. Producing pellets on site is efficient and convenient. TOMCO<sub>2</sub> Systems' pelletizers are designed in four models to meet your specific needs. Various size die diameters are available to produce pellets that are best suited to your industry. (1/8" through 3/4" nominal diameter; 2.9mm–19mm)



TOMCO<sub>2</sub> Systems' dry ice pellets have a wide variety of uses, including cleaning, food and seafood processing, field processing locations, transportation, airline service and catering. A TOMCO<sub>2</sub> Systems' sales technician can help you determine your pelletizing needs. These models are approved by the United States Department of Agriculture (USDA) for the food processing industry. All models are available with CE Mark. There is a nominal increase in dimensions for CE pelletizers.

### Model T-120-P

#### STANDARD SERIES (Available with CE mark)

**Production Rate:** 120 lbs/hr (54 kg/hr)

**Pellet Size:** Standard 1/8" (3mm) diameter and random lengths

**Drive Media:** Hydraulic 2.15 HP(1.6kW)

**Electrical Characteristics:** 480 V, 60 Hz, 3 Ph.+ PE (other voltages available upon request)

**Overall Dimensions (LxWxH):** 45.28" x 23.62" x 27.56"

**Approximate Shipping Weight:** 324 lbs (147 kg)

**NOTE:** Hydraulic Oil Not Included with Pelletizers

Model	Nominal Capacity	Metric
T-120-P	120 lbs/hr	54 kg/hr

### Model T-600-P

**Production Rate:** 600 lbs/hr (272 kg/hr)

**Pellet Size:** Standard 1/8" (3 mm) diameter and random lengths

**Drive Media:** Hydraulic 7.51 HP(5.6kW)

**Electrical Characteristics:** 480 V, 60 Hz, 3 Ph.+ PE (other voltages available upon request)

**Overall Dimensions (LxWxH):** 61.42" x 31.50" x 57.09"

**Approximate Shipping Weight:** 1,080.26 lbs (490 kg)

**NOTE:** Hydraulic Oil Not Included with Pelletizers

Model	Nominal Capacity	Metric
T-600-P	600 lbs/hr	272 kg/hr

### T-1000-P Features

**Production Rate:** 1000 lbs/hr (454 kg/hr)

**Pellet Size:** Standard 1/8" (3 mm) diameter and random lengths

**Drive Media:** Hydraulic 30 HP

**Electrical Characteristics:** 230/460 V, 60 Hz, 3 Ph. Color Touch Screen Display

**Overall Dimensions (LxWxH):** 112" x 52" x 81" (285 cm x 132 cm x 206 cm)

**Approximate Shipping Weight:** 6,500 lbs (2,948 kg)

**NOTE:** Other electrical requirements and pellet sizes available upon request. Hydraulic Oil Not Included

Model	Nominal Capacity	Metric
T-1000-P	1000 lbs/hr	453 kg/hr

### T-1500-P Features

**Production Rate:** 1,500 lbs/hr (680 kg/hr)

**Pellet Size:** Standard 3/4" (19 mm) diameter and random lengths (other sizes available upon request)

**Drive Media:** Hydraulic 30 HP

**Electrical Characteristics:** 230/460 V, 60 Hz, 3 Ph. Color Touch Screen Display

**Overall Dimensions (LxWxH):** Approx. 120" x 52" x 81" (305cm x 132cm x 206 cm)

**Approximate Shipping Weight:** Approx. 6,000 lbs (2,722 kg)

**NOTE:** Other electrical requirements and pellet sizes available upon request. Hydraulic Oil Not Included

Model	Nominal Capacity	Metric
T-1500-P	1,500 lbs/hr	680 kg/hr